An-Najah National University Faculty of Graduate Studies

# Modification of the Kawasaki's Analytic Function in Binary Liquid Mixtures

By

Rowaida Mahmoud Eisa Sadeq

Supervisor Prof. Issam Rashid Abdelraziq

Co-Supervisor Prof. Mohammed Abu-Jafar

This Thesis is Submitted in Partial Fulfillment of the Requirements for the Degree of PhD in Physics, Faculty of Graduate Studies, An-Najah National University- Nablus, Palestine.

## Modification of the Kawasaki's Analytic Function in Binary Liquid Mixtures

### By Rowaida Mahmoud Eisa Sadeq

This thesis was defended successfully on 10/04/2019 and approved by:

### **Defense Committee Members**

	<u>Signature</u>
1. Prof. Issam Rashid Abdelraziq / Supervisor	
2. Prof. Mohammed Abu-Jafar / Co-Supervisor	
3. Prof. Imad Ahmad Barghouthi/ External Examiner	
4. Prof. Sharif Musameh/ Internal Examiner	
5. Prof. Mohammed El-Saeed/Internal Examiner	

#### **Dedication**

I dedicate this project to Almighty Allah my creator. He has been the source of my strength throughout my life. I also dedicate this work to my beloved parents, who have been my source of inspiration and gave me strength when I thought of giving up, who continually provide their moral, spiritual, emotional, and financial support. To my husband who has encouraged me all the way, and whose encouragement has made sure that I give it my all to finish that which I have started. To my children Tala, Lamar and to my twin Amr and Mohammad. To my brothers, sisters, relatives, mentors, friends. Lastly, I dedicate this thesis to everyone who loves science.

#### Acknowledgement

I would like to express my greatest thanks and gratitude to my supervisors,

Prof. Issam Rashid Abdelraziq and Prof. Mohammed Abu-Jafar for their helpful efforts.

I must express my gratitude to my parents, sibling and to my husband providing me with unfailing support and continuous encouragement throughout my years of study and through the process of researching and writing this thesis. This accomplishment would not have been possible without them. Thanks for all your encouragement!

## الإقرار

انا الموقع ادناه مقدم الرسالة التي تحمل العنوان:

## Modification of the Kawasaki's Analytic Function in Binary Liquid Mixtures

اقر بان ما اشتملت عليه الرسالة انما هو نتاج شخصي باستثناء ما تمت الاشارة اينما ورد، وان هذه الرسالة ككل او جزء منها لم يقدم من قبل لنيل اي درجة او بحث علمي او بحث لدى مؤسسة تعليمية او بحثية اخرى.

### Declaration

The work provided in this thesis, unless otherwise referenced, is the researcher's own work, and has not been submitted elsewhere for any other degree or qualification.

Student's Name:	اسم الطالب :
Signature:	التوقيع :
Date:	التاريخ :

## **Table of Contents**

No.	Contents	Page	
	Dedication	iii	
	Acknowledgement	iv	
	Declaration	v	
	Table of Contents	vi	
	List of Tables	vii	
	List of Figures	viii	
	List of Abbreviations	X	
	Abstract	xii	
	Chapter One: Introduction	1	
1.1	Literature Review	1	
1.2	Objectives and Motivations	5	
1.3	Experimental technique		
1.4	Dissertation Organization	6	
	Chapter two: Theory		
	Theory	7	
	Chapter Three: Methodology	16	
3.1	The characteristics of the binary mixture	16	
	components		
3.2	Statistical Analysis	17	
	Chapter Four: Results and Discussion	18	
	Chapter Five: Conclusion	37	
	References	39	
	الملخص	ب	

## List of Tables

NO.	Contents	Page		
Table (1)	The values of different physical properties			
	that have been measured or calculated for the			
	binary mixture of nitroethane and isooctane,			
	which are found in this work and other			
	works.			

# List of Figures

NO.	Contents	Page		
<b>Fig.</b> (1)	Temperature dependence of $\alpha f^{-2}$ for the critical			
	binary mixture of nitroethane- isooctane.			
<b>Fig.</b> (2)	The absorption ( $\alpha_c f^{-2}$ ) versus f <sup>-1.06</sup> at T <sub>c</sub> and	20		
	critical mixture for nitroethane- isooctane.			
Fig. (3)	The plot of $\frac{(\alpha_{fl}f^{-2})}{(\alpha_c f^{-2})} = F(\Omega)$ versus the reduced	21		
	frequency $\Omega$ .			
<b>Fig. (4)</b>	The surface of ultrasonic attenuation absorption	24		
	coefficient as a function of temperature and			
	frequency.			
<b>Fig.</b> (5)	The experimental absorption values of $\frac{\pi}{\pi u^2(\omega)A(T)}$	25		
	versus the reduced frequency $\omega^*$ for Nitroethane			
	and Isooctane binary mixture at 5, 7, 10, 15, 21 and			
	25 MHz frequencies according to Fixmen theory			
	along with the theoretical scaling integral $F(\omega^*)$ .			
<b>Fig.</b> (6)	The experimental absorption values of	26		
	$F(\omega *) = \frac{\alpha_{\lambda}}{\pi u^2(\omega)A(T)}$ versus the reduced frequency			
	$\omega^*$ for Nitroethane and Isooctane binary mixture at			
	5, 7, 10, 15, 21 and 25 MHz frequencies according			
	to Kawasaki and Shiwa theory along with the			
	theoretical scaling integral $F(\omega^*)$ .			
<b>Fig.</b> (7)	The experimental absorption values of	27		
	$F(\omega *) = \frac{\pi}{\pi u^2(\omega)A(T)}$ versus the reduced frequency			
	$\omega^*$ for Nitroethane and Isooctane binary mixture at			
	5, 7, 10, 15, 21 and 25 MHz frequencies according			
	to Hornowski and Labowski theory along with the			
	theoretical scaling integral $F(\omega^*)$ .			
<b>Fig.</b> (8)	The experimental absorption values of	28		
	$F(\omega *) = \frac{\omega_A}{\pi u^2(\omega)A(T)}$ versus the reduced			
	frequency $\omega^*$ for Nitroethane and Isooctane binary			
	mixture at 5, 7, 10, 15, 21 and 25 MHz frequencies			
	according to Mistura theory along with the			
	theoretical scaling integral $F(\omega^*)$ .			
Fig. (9)	The experimental absorption values of $F(\omega *) = \frac{\alpha_{\lambda}}{\pi u^2(\omega)A(T)}$ versus the reduced frequency	29		

	$\omega^*$ for Nitroethane and Isooctane binary mixture at			
	5, 7, 10, 15, 21 and 25 MHz frequencies according			
	to Chapan theory along with the theoretical scaling			
	integral F( $\omega^*$ ).			
<b>Fig.</b> (10)	Kawasaki's experimental data of the absorption	31		
	attenuation coefficient per wavelength $\alpha_{\lambda}$ at critical			
	concentration at different frequencies 5, 7, 10, 15,			
	21 and 25 MHz for the binary mixture Nitroethane-			
	Isooctane versus the reduced frequency $\omega^*$			
	frequencies according to the general modification for the analytic function $K(y, \omega^*)$ [equation 25].			
<b>Fig.</b> (11)	Fixmen's experimental data of the absorption	32		
	attenuation coefficient per wavelength $\alpha_{\lambda}$ at critical			
	concentration at different frequencies 5, 7, 10, 15, 21			
	and 25 MHz for the binary mixture Nitroethane-			
	Isooctane versus the reduced frequency $\omega^*$			
	a\ccording to the general modification for the			
	analytic function $K(y, \omega^*)$ .			
<b>Fig.</b> (12)	The experimental data of absorption values of $F(\omega^*)$	33		
	$= \frac{u_{\lambda}}{\pi u^{2}(\omega)A(T)}$ versus the reduced frequency $\omega^{*}$ for			
	Nitroethane and Isooctane binary mixture at 5, 7, 10,			
	15, 21 and 25 MHz frequencies according to the new			
	modified Hornowski model of $k_{mH}(y, \omega^*)$ .			
	The experimental data of absorption values of	34		
<b>Fig.</b> (13)	$F(\omega^*) = \frac{\alpha_{\lambda}}{\pi u^2(\omega)A(T)}$ versus the reduced frequency			
	$\omega^*$ for Nitroethane and Isooctane binary mixture at			
	5, 7, 10, 15, 21 and 25 MHz frequencies according			
	to the new modified Mistura model of $k_{mM}(y, \omega^*)$ .			
	The experimental data of absorption values of	35		
<b>Fig.</b> (14)	$F(\omega^*) = \frac{\alpha_{\lambda}}{\pi u^2(\omega)A(T)}$ versus the reduced frequency			
	$\omega^*$ for Nitroethane and Isooctane binary mixture at			
	5, 7, 10, 15, 21 and 25 MHz frequencies according			
	to the new modified Chapan model of $k_{mC}(y, \omega^*)$ .			

## **Table of Abbreviations**

ACN	pure acetonitrile		
FA	Formamide		
gm	Gram		
K°	Kelvin		
$\omega^*, \Omega$	the reduced frequency		
GHz	Giga Hertz		
Db	Decibel		
mgm	Milligram		
$f(\boldsymbol{\omega}^*)$	the scaling function		
H	the critical amplitude		
$u(\omega)$	the velocity of sound wave		
$\alpha f^{-2}$	the experimental data of sound absorption, which is a		
	function of frequency and temperature; is the fluctuation		
	absorption, related to the processes in the mixture, when		
	approaching the critical temperature $T_c$		
$\alpha_{reg}f^{-2}$	the regular absorption, related to the structural features of		
-	the tested mixtures without fluctuations		
$\alpha_{fl}f^{-2}$	the critical ultrasonic attenuation absorption coefficient		
	fluctuation at critical concentration and temperature T		
	related to the processes in the mixture, when approaching		
- 7	the critical temperature		
$\alpha_c f^{-2}$	the critical term of ultrasonic attenuation absorption		
	coefficient at critical temperature $T_c$ and critical		
	composition		
$ au_1$	the dispersive area relaxation time		
A <sub>1</sub>	the relaxation area amplitude		
<i>m</i> , <i>n</i> , <i>s</i>	Indexes		
$F(\omega *)$	the scaling function introduced		
$\omega_D$	the characteristic relaxation frequency of concentration		
	fluctuations		
$\alpha_t$	the critical exponent of the isochoric heat capacity		
n	the critical exponent of the correlation length		
	characterizing its dependence on temperature		
Z	the dynamic critical exponent		
$c_p(t_f)$	the specific heat at a characteristic reduced temperature		
	$t_f$ .		
a	dimensionless scaling factor of order unity		
$\omega_0$	characteristic temperature dependent relaxation rate		

**g** adiabatic coupling constant

Cpc	The critical amplitude for the specific heat at constant			
	pressure of binary mixture at critical concentration			
Cpb	the background specific heat			
$\rho_c$	The density at critical temperature and concentration			
t	the reduced temperature			
$\alpha_P$	the isobaric thermal expansion coefficient			
$lpha_{pc}$	the critical thermal expansion coefficient			
$lpha_{pb}$	the background thermal expansion coefficient			
F(ω *)	the theoretical scaling function			
ω	the angular frequency			
ω <sub>D</sub>	characteristic temperature-dependent relaxation rate			
D	the mass diffusion coefficient			
ξ	the correlation length			
ξo	the critical amplitude of the correlation length			
μ	the dynamic shear viscosity			
$x_{\mu}, \nu$	are the critical exponent			
$\mu_0$	the noncritical part of the dynamic shear viscosity			
$\mathbf{D}_{0}$	the diffusion coefficient			
$\omega^*_{1/2}$	the half attenuation frequency			
αλ	the ultrasonic attenuation absorption coefficient per			
	wavelength at critical concentration			
q	the wave number			
KB	the Boltzmann's constant			
γ	the critical exponent			
K(y)	the analytic function			
γo	the ratio of heat capacities			
$dT_c$	is the slope line of the critical line of consolute points as a			
dP	function of pressure			
d	a dimensionless parameter			

### Modification of the Kawasaki's Analytic Function in Binary Liquid Mixtures By Rowaida Mahmoud Eisa Sadeq Supervisor Prof. Issam Rashid Abdelraziq Co-Supervisor Prof. Mohammed Abu-Jafar

#### Abstract

The temperature dependence of the ultrasonic attenuation absorption coefficient at critical composition and above critical temperature T<sub>c</sub> for the binary mixture nitroethane-isooctane at 5, 7, 10, 15, 21, and 25 MHz frequencies (f) is investigated. In addition, the linear relation of the ultrasonic attenuation absorption coefficient at critical point  $(\alpha_c)/f^2$  versus  $f^{-1.06}$  showed an excellent agreement with the dynamic scaling theory of Ferrell and Bhattacharjee. The experimental values of  $\left(\frac{\alpha f^{-2}}{\alpha_{r} f^{-2}}\right)$  for nitroethane-isooctane binary mixture are plotted as a function of reduced frequency  $\omega^*$  and it showed a good agreement with the theoretical scaling function  $F(\omega^*)$ . Furthermore, Fixmen, Kawasaki, Hornowski, Mistura, and Chapan function failed to explain the experimental behavior of the binary liquid mixtures at critical composition and above critical temperature according to mode coupling theories. In this thesis we corrected the analytic function of Fixmen's, Kawasaki's, Hornowski's, Mistura's, and Chapan's theories was corrected in order to get an agreement with the experimental behavior of the binary liquid mixtures at critical composition and above the critical temperature.

## **Chapter One**

## Introduction

A sound wave is a longitudinal, mechanical pressure wave; regions of high pressure are compressions and low-pressure regions are rarefactions.

Binary liquid mixtures are a system consists of two pure liquid substances, which have a limited solubility of each one in the other [1]. The point at which binary system behaves the same homogenous phase under the same condition, pressure, specific heat, viscosity, and thermal conductivity is the critical point of binary mixture. This point illustrates the boundary between areas of homogeneous and heterogeneous behavior in phase diagrams for binary mixtures [2]. Binary liquid mixtures has many applications in engineering, biological and industrial processes present a wide choice of solutions with suitable properties. Ultrasonic can be a useful tool for gaining qualitative information of some physical parameters in these binary liquid mixtures [3].

#### **1.1 Literature Review**

Theoretical and experimental studies of critical binary mixtures, near the critical separation temperature  $T_c$  are a topic of lively scientific debates [4–8], they cover a wide range of unique and universal properties of such systems and their practical use [9-11]. A multiple of thermodynamic properties have been calculated by studying the attenuation of ultrasonic waves through liquids [5,12-19].

Densities and ultrasonic speeds of pure acetonitrile (ACN) 1-butanol, formamide (FA) and those of eighteen binary mixtures of ACN with 1butanol and FA were measured at 30gm. and 15 K°[20]. Also, isentropic compressibility, intermolecular free length, relative association, acoustic impedance, molar sound speed, excess isentropic compressibility, excess intermolecular free length, excess volume, deviation in ultrasonic speed and excess acoustic impedance were calculated using different theories and relations from the experimental data [20].

The critical behavior of sound propagation through absorption or dispersion for different binary liquid mixtures at critical composition and above critical temperature have been studied by scientists and researchers [21-50]. The most important models that discussed the behavior of sound waves propagation are the renormalization group theory by kroll and Ruhland [50], the dynamic scaling theory by Ferrell and Bhattacharjee [16] and a package of mode- coupling theory by Fixmen [51], Kawasaki and Shiwa [52], Chapan [53], Mistura [54], and Hornowski [55]. These theories failed to describe the experimental data over a wide range of the reduced frequency  $\omega^*$ . These theories are based on the view that understanding the fluctuations that occur in those binary mixture rather than focus on microscopic aspects [56-58]. Kawasaki mode-Coupling theory was developed in terms of critical behavior of bulk viscosity. Kawasaki studied theoretically the sound attenuation and dispersion using the extended mode-mode coupling theory [52]. Hornowski and Labowski [55] applied the modified version of the mode coupling theory for the acoustic anomaly based on the critical behavior of a relaxing complex heat capacity.

Guixiang Ma and his group investigated the thermal properties and thermal reliability of stearic acid-n-butyramide and stearic acid-noctanamide binary eutectic mixtures, as phase change materials for low temperature solar heat energy storage. The solid-liquid phase diagrams of two binary systems were established and the eutectic compositions of binary mixtures and corresponding thermal properties were verified: (1) stearic acid-nbutyramide, the eutectic composition is  $0.551 \pm 0.005$  mol fraction stearic acid and (2) stearic acid-noctanamide,the eutectic composition is  $0.589 \pm 0.005$  mol fraction stearic acid. The mixture has a good thermal stability after 100 melt-freeze cycles. As novel phase change materials for solar heat applications, the studied eutectic mixtures have attractive thermal performance and great utility [59].

Abdelraziq [40-48] developed the modified mode-coupling theory by Hornowski [55] to describe the critical attenuation of the binary system of Aniline and cyclohexane. He found that there is poor agreement between this modification and experimental data above 10 MHz of reduced frequency. Latifa and his group showed that current theories cannot describe the velocity  $u(\omega)$  and absorption of hypersound in critical mixtures at frequencies above 4 GHz [37]. A lot of the thermodynamic properties of the solution process, including the Gibbs free energy, enthalpy, and entropy were calculated for different binary liquid mixtures at different temperatures [60- 67].

Volumetric and ultrasonic properties of ionic liquids, speed of sound, the density values were used to calculate excess molar volume, whereas speed of sound results have been used to calculate deviation in isentropic compressibility. The excess properties and spectroscopic data have been analyzed in terms of the effect of temperature and the change of the anion of ionic liquid [68, 71].

The ultrasonic absorption and velocity  $u(\omega)$  measurements were studied as a function of temperature and frequency for different binary mixtures, the viscosity and many thermodynamic properties were measured [20-62]. Densities and viscosities of different ionic liquids were measured by Dongren Cai et al, [72] at different temperatures as a function of molality (or mass fraction). The isobaric thermal expansion coefficient, molecular volume, standard molar entropy, and lattice energy of the pure ionic liquid were obtained based on the density data of pure ionic liquid [72]. The apparent molar volume, infinite dilution apparent molar expansibility, and energy barrier were calculated from the experimental data [72].

The shear behavior of binary mixtures via a two-dimensional discrete element method was investigated by Gong and Liu [73]. The effect of the coarse particle content on the peak shear strength of mixtures is investigated for different contact-type friction coefficients. The interparticles structures are examined when the binary mixtures become coarse-particle-supported structures [73]. The excess heat capacities were calculated from the measured molar heat capacities data of the binary as well as ternary mixtures at different temperatures by Sharma et al [74].

#### **1.2.** Objectives and Motivations

The aim of the present investigation is to compare the experimentally determined ultrasonic attenuation absorption coefficient in binary liquid mixtures with Kawasaki mode coupling theory. In order to have an agreement between the theoretical and experimental data for the ultrasonic attenuation absorption coefficient in binary liquid mixtures, it is necessary to predict a new suitable formula for Kawasaki analytic function.

#### **1.3. Experimental technique**

Measurements of absorption and velocity  $u(\omega)$  are made using Matec pulse – echo technique. The following Matec equipment was used: a radio frequency gated amplifier model 515, which is a plug-in unit of Matec gating modulator model 5100, a doubled turned –amplifier model 252, a broadband receiver model 605 and model 666 pulse-comparator, which generates a pulse of radio frequency energy, which can be precisely controlled in amplitude in steps of 0.1dB up to a total of 61dB. The sample was prepared by the weight using an Ohaus 1600 series balance and Sartorius scale which has a precision of 0.05 mg. The purification of chemicals was 99.9%. The absorption and velocity  $u(\omega)$  of sound were measured above the critical temperature and shaken several times to ensure complete mixing. The test cell was also heated above the critical temperature before the sample was added. The pulse comparator was used to measure the height of the echoes viewed on the oscilloscope. For a given number of interference peaks, the displacement of the reflector, which leads to the wavelength, is measured and used with the frequency to determine the velocity of sound  $u(\omega)$  in liquid.

#### **1.4. Dissertation Organization**

The thesis is divided of five chapters. Chapter one is the introduction which presents a review of ultrasonic studies in different liquid mixtures. Chapter two discusses the mode-coupling theories of Fixmen, Kawasaki and Shiwa, Mistura, Chapan, and Hornowski which was applied for analyzing the ultrasonic information. Methodology of the work is shown in chapter three, while the measured data and the results are shown in chapter four. Conclusions are presented in chapter five.

### **Chapter two**

#### Theory

Ultrasonic attenuation is the decay rate of the sound wave as it propagates through material. There are many theoretical models that have discussed the ultrasonic attenuation through binary liquid mixtures at the critical points. Kroll D. M. and Ruhaland J. M. [50] have studied a model for sound propagation in critical binary mixtures using renormalization-group theory and expansion methods. The basis of this theory is to describe the behavior of ultrasonic propagation in the existence of consolute point to calculate the bulk viscosity. The only significant contribution to the bulk viscosity comes directly from order-parameter fluctuations, and renormalization-group theory. New scaling relations for the critical attenuation and dispersion are obtained, the critical ultrasonic attenuation absorption coefficient per wavelength was written as the following [50]:

$$\frac{\alpha_{\lambda}(crit)}{u^{2}(\omega)} = \pi H \, Im \, F(\omega^{*}) \tag{1}$$

Where  $\alpha_{\lambda}(crit)$  is the critical ultrasonic attenuation absorption coefficient per wavelength,  $F(\omega^*)$  is the scaling function, H is the critical amplitude,  $u(\omega)$  is the velocity of sound wave, and  $\omega^*$  is the reduced frequency. Scientists used renormalization group theory [50] in order to explain the critical behavior of binary mixture. Taking into account the theory of dynamic scaling theory [16, 73-75], the ultrasonic attenuation absorption coefficient  $\alpha f^{-2}$  is the sum of regular and fluctuation components [76]:

$$\alpha f^{-2} = \alpha_{reg} f^{-2} + \alpha_{fl} f^{-2} \tag{2}$$

where  $\alpha f^{-2}$  is the experimental data of sound absorption, which is a function of frequency and temperature;  $\alpha_{reg}f^{-2}$  is the regular absorption, related to the structural features of the tested mixtures without fluctuations;  $\alpha_{fl}f^{-2}$  is the fluctuation absorption, related to the processes in the mixture, when approaching the critical temperature  $T_c$ .

Regular absorption connected with the changes in the molecular structure of the mixture by conformation processes, formation of associates, dimers or complexes, is described by the formula with one relaxation area for binary mixtures in the test frequency range [77, 78].

$$(\alpha f^{-2})_{reg} = \left[\frac{A_1}{(1+(\omega\tau_1)^{2S})^{\frac{m+n}{2S}}}\right]$$
(3)

where  $\omega = 2\pi f$  is the angular frequency;  $\tau_1$  is the dispersive area relaxation time;  $A_1$  is the relaxation area amplitude; indeces *m*, *n*, *s* equal (0,1], introduced by Hill [77] to take account of collective processes, determine the ultrasonic attenuation absorption coefficient frequency dependence. For the test mixture m=n=s=1. Fluctuation component analysis was performed using Ferrel and Bhattacharjee [16] theory of relaxing heat capacity

$$(\alpha_{fl}f^{-2}) = (\alpha_c f^{-2})F(\omega *) \tag{4}$$

Where  $\alpha_c f^{-2}$  is the ultrasonic attenuation absorption coefficient t at critical point, and  $F(\omega *)$  is the scaling function introduced by the authors [16];  $\omega *$  is the scaled frequency  $\omega *=\frac{\omega}{\omega_D} = \frac{2\pi f}{\omega_0 t^{zv}}$ ,  $\omega_D$  is the characteristic relaxation frequency of concentration fluctuations, v is the critical exponent of the correlation length characterizing its dependence on temperature; z is the dynamic critical exponent.

Dynamic scaling theory in binary mixture is based on the dependent specific heat concept. frequency The total critical ultrasonic attenuation absorption coefficient the critical at temperature and concentration in the dynamic scaling theory by Ferrell and Bhattacharjee can be expressed as [16]:

$$(\alpha_c f^{-2}) = S.f^{-\left[1 + \frac{\alpha_t}{zv}\right]} + \alpha_b f^{-2}$$
(5)

where  $\alpha_c f^{-2}$  - is the ultrasonic attenuation absorption coefficient at critical point,  $\alpha_t$  is the critical exponent of the isochoric heat capacity (a subindex t is used not to take the exponent for the absorption coefficient  $\alpha$ ); S is the amplitude of frequency dependence of the singular part of the ultrasonic attenuation absorption coefficient  $\alpha_t$ =0.11 and  $z\nu$  = 1.9 are the critical exponents [40].

The S value is given by Ferrell and Bhattacharjee [16].

$$\mathbf{S} = \left[\frac{\{\pi C_{pc} g^2 u(\omega) \alpha_t\}}{\{2zv T_c C_p^2(t_f)\}}\right] \left[\frac{a\omega_0}{2\pi}\right]^{\frac{\alpha_t}{zv}}$$
(6)

Where  $c_p(t_f)$  is the specific heat at a characteristic reduced temperature  $t_f$ , a =  $(\frac{\omega}{\omega_0})^t f^{-zv}$  is dimensionless scaling factor of order unity,  $\omega_0$  is characteristic temperature dependent relaxation rate, g is adiabatic coupling constant,  $u(\omega)$  is the adiabatic sound velocity at T<sub>c</sub>. The critical amplitude for the specific heat at constant pressure of binary mixture at critical concentration, C<sub>pc</sub> is represented by [78,79]:

$$C_p = c_{pc} t^{-\alpha_t} + c_{pb} \tag{7}$$

Here  $C_{pb}$  is the background specific heat thermal expansion coefficient. The adiabatic coupling constant g is presented to verify the subdivision in

attenuation spectra into the critical contribution and the sophisticated background contribution. The adiabatic coupling constant g depends on pressure, temperature and isobaric thermal expansion coefficient. The g factor may be negative or positive. The negative sign of g factor indicates that the phase separation near the critical point is induced by a sudden decrease in the pressure. The positive sign for the g factor indicates that the phase separation near the critical point is induced by a sudden the pressure. The adiabatic coupling constant is given by [79]:

$$g = \rho_c C_p \left[ \frac{dT_c}{dP} - \frac{T\alpha_p}{\rho_{c_p}} \right] \cong \frac{C_{pb} \alpha_{pc} T_c}{C_{pc}} - \alpha_{pb} T$$
(8)

where  $\rho_c$  is the density at critical temperature and concentration; the reduced temperature t is represented by:  $t = \frac{T - T_c}{T_c}$ ;  $\alpha_p$  is the isobaric thermal expansion coefficient which is given:

$$\alpha_p = \alpha_{pc} t^{-\alpha_t} + \alpha_{pb} \tag{9}$$

Note that  $\alpha_p$  is the isobaric thermal expansion coefficient,  $\alpha_{pc}$ and  $\alpha_{pb}$  are the critical background parts of the thermal expansion coefficient,  $\alpha_{pc}$  is the critical thermal expansion coefficient and  $\alpha_{pb}$  is the background thermal expansion coefficient.  $C_p(t_f)$  is the specific heat at a characteristic reduced temperature  $t_f$ . The critical term of the absorption can be represented as a function of the dimensionless reduce frequency  $\Omega$  or  $\omega^*$  which is [40, 16]:

$$\left(\frac{\alpha_{fl}f^{-2}}{\alpha_c f^{-2}}\right) = F(\omega *) \tag{10}$$

 $\alpha_{fl}f^{-2}$  is the critical absorption at critical concentration and temperature T, while  $\alpha_c f^{-2}$  is the critical term at critical T<sub>c</sub> and critical composition. F( $\omega *$ ) is the theoretical scaling function.

where  $\omega$  is the angular frequency,  $\omega_D$  is a characteristic temperature-dependent relaxation rate that can be approximated by Stokes- Einstein expression:  $\omega_D = 2D\xi^{-2}$  where D is the mass diffusion coefficient and [54]:

$$\omega_D = \frac{K_B T}{3\pi\mu\xi^3} = \frac{K_B T_C}{3\pi\mu_0\xi_0^3} t^{Z\nu} = \omega_0 t^{Z\nu}$$
(11)

Using the relationships  $\omega_0 = 2D_0\xi_0^{-2}$ , for the correlation length  $\xi = \xi_0 t^{-\nu}$  and the dynamic shear viscosity  $\mu = \mu_0 t^{-x_{\mu}\nu}$ . While  $\xi_0$  is the critical amplitude of the correlation length,  $x_{\mu}$ ,  $\nu$  are the critical exponent [40] ( $\nu = 0.64$ ,  $-x_{\mu}\nu = 0.037$ );  $\mu_0$  is the noncritical part of the dynamic shear viscosity whereas  $D_0$  is the diffusion coefficient.

Taking into account theoretical expression for crossover function [16].

$$F(\omega *) = \frac{1}{\left[1 + 0.414 \langle \frac{\omega *_{1/2}}{\omega *} \rangle^n\right]^2}$$
(12)

Where  $\omega^*_{1/2}$  is the reduced half attenuation frequency.

the final formula for ultrasonic attenuation absorption coefficient fluctuation looks like

$$\left(\alpha_{fl}f^{-2}\right) = S.f^{-\left[1+\frac{\alpha_{t}}{z_{\nu}}\right]} \left[1+0.414\left(2\pi f.\omega*_{1/2}\tau_{fl}\right)^{-n}\right]^{-2}$$
(13)

allowing the finding of relaxation time of concentration fluctuation in the test solution according to the experimental data of the ultrasonic attenuation absorption coefficient for different temperatures near the critical point.

The final model discussed in this research is the mode coupling theories developed by Fixmen [51], Kawasaki and Shiwa [52, 53], Mistura and Chapan [54], and Hornowski [55].

The mode-coupling theories by Fixmen, Mistura, Chapan, Kawasaki and Shiwa lead to the same general expression for the ultrasonic attenuation absorption coefficient per wavelength  $\alpha_{\lambda}$  at critical concentration [51-55]:

$$\frac{\alpha_{\lambda}}{u^{2}(\omega)} = \pi A(T)F(\omega *)$$
(14)

where A(T) is the critical amplitude which is different for each theory,  $u(\omega^*)$  is the velocity  $u(\omega)$  of sound, and F( $\omega^*$ ) is the scaling function. The general form of the scaling function is given by equation (2) [51-55]:

$$F(\omega^*) = \int \{ \left[ \frac{y^2 \, dy}{(1+y^2)^2} \right] \left[ \frac{\omega^{*K}(y)}{K(y)^2 + \omega^{*2}} \right] \}$$
(15)

Where  $y = q\xi$ , q is the wave number and  $\xi = \xi_0 t^{-\nu}$  is the correlation length, while  $\xi_0$  is the critical amplitude of the correlation length, the reduced temperature t,  $T_c$  is the critical temperature of the binary mixture,

K(y) is the analytic function. In Fixman model the analytic function K(y) is given by [51]:

$$K(y) = y^{2} [1 + y^{2}]$$
(16)

While Kawasaki's analytic function is given by[52]:

$$K(y) = \frac{3}{4} \left[ 1 + y^2 + (y^3 - \frac{1}{y})tan^{-1}(y) \right] \left[ 1.055^a + \{0.93 + 0.29\log_{10}(y)\}^a \right]_a^{\frac{1}{a}}$$
(17)  
With fitting exponent a = 13.

The Mistura's and Chapan's analytic function is [54].

$$K(y) = \frac{3}{4} \left[ 1 + y^2 + (y^3 - \frac{1}{y})tan^{-1}(y) \right]$$
(18)

The critical amplitudes A(T) of the binary mixture in the mode-coupling theories are given as follows:

Fixman's and Kawasaki's critical amplitudes  $A_F(T)$  and  $A_K(T)$  are given by [44, 51, 52]:

$$A_{F}(T) = A_{K}(T) = \left[\frac{K_{B}(\gamma_{0}-1)\nu^{2}}{\pi\rho u C_{Pb}\xi_{0}^{3}}\right]t^{-\alpha}$$
(19)

Where  $K_B$  is Boltzman's constant,  $\rho$  is the density of the mixture,  $C_{Pb}$  is background heat capacity at constant pressure,  $\gamma_0 = \frac{c_P}{c_V}$  is the ratio of heat capacities,  $\xi_0$  is the correlation length. The form of Mistura's critical amplitude is given by [54, 44]:

$$A_{\rm M}(T) = A_{\rm F}(T) \left[\gamma_0 - 1\right]^{-2} \left[1 - 0.5\eta\right]^2 \tag{20}$$

Chaban's form  $A_C(T)$  is given by [54, 44]:

$$A_{C}(T) = A_{F}(T) \left[ 1 - \left(\frac{\rho C_{Pb}}{\alpha_{Pb}}\right) \left(\frac{dT_{c}}{dP}\right) \right]^{2}$$
(21)

 $\alpha_{Pb}$  is the background amplitude of the thermal expansion,  $\frac{dT_c}{dP}$  is the slope of the critical line of consolute points as a function of pressure, and  $\eta$ , v,  $\alpha$  are critical exponents which equal to 0.04, 0.62, 0.11, respectively [44].

Hornowski and Labowski [55] applied the modified version of the mode coupling theory for the acoustic anomaly based on the critical behavior of a relaxing complex heat capacity. The general expression for the critical amplitude  $A_H(T)$  is given by:

$$A_{H}(T) = A_{K}(T)[1 - 0.5\eta]^{2}f(d)$$
(22)

Where  $\eta$  is a critical exponent = 0.04, d is a dimensionless parameter  $d = \left[\frac{\rho C_{Vb}}{\tau \alpha_{Pb}}\right] \left[\frac{dT_c}{dP}\right]$  and the function f(d) is given by:

$$f(d) = |(\gamma_0 d - 1)^2 - 2d\gamma_0 [d - (\gamma_0 - 1)^{-1}]|$$
(23)

 $C_{vb}$  is background heat capacity coefficient and  $\alpha_{pb}$  is background thermal expansion coefficient.

# Chapter Three Methodology

The binary liquid mixture nitroethan-isooctane system has a chemical form of  $C_2H_5NO_2$  -  $C_8H_{18}$ , it has a critical temperature of  $Tc = 31.5^{\circ}C$  at critical composition of 0.50356 by weight of isooctane.

#### **3.1** The characteristics of the binary mixture components

The binary mixture used in this research consists of the compounds nitro ethane and isooctane, nitro Ethan is a colorless oily liquid with a pleasant odor. Flash point of 27.78C°. Decomposes above 350F°. Density is 1.052  $g / cm^3$ . Vapors are much heavier than air. It is insoluble in water. Vapor may irritate skin, eyes and mucous membranes, produces toxic oxides of nitrogen during combustion. It is used as a propellant and as a solvent, nitroethane is a nitroalkane that is ethane substituted by a nitro group. It is a tautomer of an aci-nitroethane. The molecular formula of nitroethan is  $C_2H_5NO_2$  or  $CH_3CH_2NO_2$  and the molecular weight is 75.067 gm/mol. Isooctan or 2,2,4-Trimethylpentane is a clear colorless liquid with a petroleum-like odor. Less dense than water and insoluble in water. Vapors are heavier than air. Isooctane is an alkane that consists of pentane bearing two methyl substituents at position 2 and a single methyl substituent at position 4. It has a role as a fuel additive, a non-polar solvent and a nephrotoxin. It is an alkane and a volatile organic compound, the molecular formula of isooctan is  $CH_3C$  ( $CH_3$ )<sub>2</sub>  $CH_2CH$  ( $CH_3$ )<sub>2</sub> or  $C_8H_{18}$ 

with molecular weight of 114.232 gm\ mol, the density of isooctane is 0.69 g/cm<sup>3</sup> (20 °C).

## **3.2 Statistical analysis**

The statistical program MATLAB is used to analyze and plot data for ultrasonic attenuation absorption coefficient for nitroethan and isooctan binary mixture.

# Chapter Four Results and Discussion

The binary mixture Nitroethane and Isooctane has a critical temperature of  $Tc = 31.5^{\circ}C$  at critical composition of 0.50356 by weight of isooctane. The ultrasonic attenuation absorption coefficient  $\alpha_{\lambda}$  at different temperatures and at 5, 7, 10, 15, 21 and 25 MHz frequencies for the critical binary mixture of Nitroethane and Isooctane were measured using the Matec pulse-echo technique that generates pulses through the temperature-controlled test cell.

Fig. 1 shows the ultrasonic attenuation absorption coefficient  $(\alpha f^{-2})$  versus temperature at different frequencies.



**Figure1:** Temperature dependence of  $\alpha f^{-2}$  for the critical binary mixture of nitroethane- isooctane.

Firstly, the regular part of the ultrasonic attenuation absorption coefficient  $(\alpha f^{-2})_{reg}$  was calculated. It was made for the processing of experimental data given on Fig.1 using formula (3) for non-critical temperature range. Experimental data for the temperature range  $\Delta T = T - T_c \ge 2K^\circ$ , where we observed anomalous absorption, was processed with the help of Mathcad.

The received results of processing equation (3) parameters dependent on the temperature for all tested mixture concentrations were approximated in the temperature range with anomalous sound absorption.

This created a possibility of receiving numeric values of ultrasonic attenuation absorption coefficient fluctuation part $(\alpha f^{-2})_{fl}$ , according to equation (2), having experimental data on the sound absorption and calculated values of regular absorption component.

The dynamic scaling theory of Ferrell and Bhattacharjee shows that  $\frac{\alpha_{fl}f^{-2}}{\alpha_{c}f^{-2}}$  should be a function of the reduced frequency  $\omega^*$ , and should be scaled with the scaling function  $F(\omega^*)$ . According to the theory  $(\alpha_{c}f^{-2})$  versus  $f^{-1.06}$  must give a straight line at the critical temperature and composition. A linear relation between the ultrasonic attenuation absorption coefficient  $(\alpha_{c}f^{-2})$  versus  $f^{-1.06}$ , at Tc = 31.5 °C and at critical composition 0.50356 by weight of isooctane for the critical binary mixture of nitroethane-isooctane, is shown in Fig. 2.



Figure 2: The absorption (  $\alpha_c f^{-2}$  ) versus f<sup>-1.06</sup> at T<sub>c</sub> and critical mixture for nitroethane- isooctane.

The slope S =  $2.13 \times 10^{-7}$  cm<sup>-1</sup>s<sup>0.94</sup> and the intercept of  $134.63 \times 10^{-17}$  cm<sup>-1</sup>s<sup>2</sup> represents the frequency independent background term of ( $\alpha_c f^{-2}$ ). The data forms a straight line as shown by Ferrell and Bhattacharjee theory.



**Figure 3:** The plot of  $\frac{(\alpha_{fl}f^{-2})}{(\alpha_c f^{-2})} = F(\Omega)$  versus the reduced frequency  $\Omega$  or  $\omega^*$ .

Processing of experimentally received scaling function by equation (13) within the bounds of Ferrel and Bhattacharjee heat capacity relaxing theory, allowed to find the parameters values of equation (13):  $n = 0.53 \pm 0.03$  and  $\Omega_{1/2} = 2.5 \pm 0.05$  [56] (in Fig. 3). The received values should be compared with results of other works: n = 0.5 and  $\Omega_{1/2} = 2.1$  [63]; n = 0.53

0.63 and  $\Omega_{1/2} = 3.1[57]$ ; n = 0.5 and  $\Omega_{1/2} = 6.2$  [58], corresponding curves [1], [2] and [3] respectively.

The experimental data of  $\frac{(\alpha_{fl}f^{-2})}{(\alpha_c f^{-2})}$  as function of the reduced frequency is in good agreement with the theoretical scaling function as assumed by Ferrell and Bhattacharjee [16].

The temperature independent relaxation rate for the critical binary mixture of nitroethane-isooctane is  $\omega_0=6.51945\times1010$  Hz and the diffusion coefficient D<sub>0</sub> equals  $1.90903\times10^{-9}$  m<sup>2</sup>/s. The adiabatic coupling constant (g) was calculated by Hornowski *et al* [55, 56] was found to be 0.356 [55, 66]. In our work the experimental adiabatic coupling constant  $g = 0.24829\pm0.00111$  and the theoretical adiabatic coupling constant g = 0.3582, were in good agreement with Hornowski team [55, 66]. The results of different properties that have been calculated or measured for the critical binary mixture of nitroethane-isooctane were compared with results from literature review presented in Table 1.

Table (1): The values of different physical properties that have been measured or calculated for the binary mixture of nitro ethane and isooctane, which are found in this work and other works.

Quantity	Measured	Calculated	References
S(cm <sup>-1</sup> S <sup>0.94</sup> ) at 35°C	2.13×10 <sup>-7</sup>	$(2.7761 \pm 0.0702372) \ge 10^{-7}$	
g at 35° <b>C</b>	0.3582	$0.24829 \pm 0.00111$	$0.356^{19}$
$\omega_0(Hz)$		6.51945×10 <sup>10</sup>	
$D_0(m^2/S)$		1.90903×10 <sup>-9</sup>	
$\frac{dT_c}{dP}(K.Pa^{-1})$			$(2.6\pm0.5)\times10^{-8}$
ξο		2.42	
$\rho_{c}(Kg/m^{3})$		813	
C <sub>Pc</sub> (J/Kg.K)		214.31	
C <sub>Pb</sub> (J/Kg.K)			1750 <sup>19</sup>

Analysis of nitroethane-isooctane critical binary mixture ultrasonic attenuation absorption coefficient temperature and frequency dependences properties as the sum of regular and fluctuation parts, for the first time allowed the making of a surface (Fig.4) as a function of concentrations fluctuations relaxation time  $\tau_{fl}$  according to the formula 24 which derived from equations 2, 3 and 14:

$$\alpha f^{-2} = S. \left[ 1 + 0.414 \cdot \left( 2\pi f \cdot \Omega_{1\backslash 2} \tau_{fl} \right)^{-2} \right]^{-2} \cdot f^{-\left[ 1 + \frac{\alpha_t}{Z\nu} \right]} + \Sigma_{i=1}^2 \left[ \frac{A_i}{\left[ 1 + (\omega \tau_i)^{2s} \right]^{\frac{m+n}{2s}}} \right] + B (24)$$



**Figure 4:** The surface of ultrasonic attenuation absorption coefficient as a function of temperature and frequency.

From equation (15) we can expect that the experimental values of  $F(\omega^*)$  depend on the amplitude A(T) and other same constants for specific binary mixture, from comparison between equations (19, 20, 21, and 22) we conclude that the experimental values for Fixmen and Kawasaki are the same so the modification will be the same for the two models.

Figures 5, 6, 7, 8, and 9 represent plots of experimental absorption attenuation values of  $F(\omega^*)$  versus the reduced frequency  $\omega^*$  for Nitroethane and Isooctane binary mixture at 5, 7, 10, 15, 21 and 25 MHz frequencies of Fixmen's, Kawasaki's, Hornowskie's, Mistura's, and Chapan's expressions respectively, along with the theoretical scaling integral  $F(\omega^*)$ .



**Figure 5:** The experimental absorption values of  $\frac{u\lambda}{\pi u^2(\omega)A(T)}$  versus the reduced frequency  $\omega^*$  for Nitroethane and Isooctane binary mixture at 5, 7, 10, 15, 21 and 25 MHz frequencies according to Fixmen theory along with the theoretical scaling integral  $F(\omega^*)$ .



Figure 6: The experimental absorption values of  $F(\omega *) = \frac{\alpha_{\lambda}}{\pi u^2(\omega)A(T)}$  versus the reduced frequency  $\omega^*$  for Nitroethane and Isooctane binary mixture at 5, 7, 10, 15, 21 and 25 MHz frequencies according to Kawasaki and Shiwa theory along with the theoretical scaling integral  $F(\omega^*)$ .



Figure 7: The experimental absorption values of  $F(\omega *) = \frac{\alpha_{\lambda}}{\pi u^2(\omega)A(T)}$  versus the reduced frequency  $\omega^*$  for Nitroethane and Isooctane binary mixture at 5, 7, 10, 15, 21 and 25 MHz frequencies according to Hornowski and Labowski theory along with the theoretical scaling integral  $F(\omega^*)$ .



**Figure 8:** The experimental absorption values of  $F(\omega *) = \frac{\alpha_{\lambda}}{\pi u^2(\omega)A(T)}$  versus the reduced frequency  $\omega^*$  for Nitroethane and Isooctane binary mixture at 5, 7, 10, 15, 21 and 25 MHz frequencies according to Mistura theory along with the theoretical scaling integral  $F(\omega^*)$ .



Figure 9: The experimental absorption values of  $F(\omega *) = \frac{\alpha_{\lambda}}{\pi u^2(\omega)A(T)}$  versus the reduced frequency  $\omega^*$  for Nitroethane and Isooctane binary mixture at 5, 7, 10, 15, 21 and 25 MHz frequencies according to Chapan theory along with the theoretical scaling integral  $F(\omega^*)$ .

The provided figures (5-9) illustrate that there is a disagreement between the theoretical and experimental data at different frequencies, because of this disagreement, we focus our efforts in this study to modify the analytic function for the mode-coupling theory in order to have an agreement between theory and the experimental data for  $F(\omega^*)$  at different frequencies and temperatures for the five mode coupling theories. The analytic function K(y) affects in the form of the scaling function  $F(\omega^*)$  as shown in equation (15). The final modified form of the analytic function  $k_m(y,\omega^*)$  is given by the relation:

$$= \frac{\omega^{*} + \omega^{*} \times \sqrt[2]{1 - 4\left[\left(\frac{y^{2} + y}{1 + y^{2}}\right) \times \left[-0.1762 \times \omega^{*-0.225} + 0.5428\right]\right]^{2}}}{2\left[\left[\frac{y^{2} + y}{1 + y^{2}}\right] \times \left[-0.1762 \times \omega^{*-0.225} + 0.5428\right]\right]}$$
(25)

Fixmen, Kawasaki, Hornowski, Mistura, and Chapan modification analytic function is applied to the binary mixture Nitroethane-Isooctane. The modified analytic function depends on the correlation length  $(y = q\xi)$  and the reduced frequency  $\omega^* = \frac{2\pi f}{\frac{k_B T}{3\pi\mu_0\xi_0^2}t^{ZV}}$  which depends on the correlation

length ( $\xi$ ) and depends also on the shear viscosity  $\mu$ .

Figures from 10 and 11 predict plots of Fixmen and Kawasaki experimental absorption attenuation values of  $F(\omega^*)$  versus the reduced frequency  $\omega^*$  for Nitroethane and Isooctane binary mixture at 5, 7, 10, 15, 21 and 25 MHz frequencies. The general modification for the analytic function is given in equation (25) along with the theoretical scaling integral  $F(\omega^*)$ .



**Figure 10:** Kawasaki's experimental data of the absorption attenuation coefficient per wavelength  $\alpha_{\lambda}$  at critical concentration at different frequencies 5, 7, 10, 15, 21 and 25 MHz for the binary mixture Nitroethane-Isooctane versus the reduced frequency  $\omega^*$  frequencies according to the general modification for the analytic function K(y,  $\omega^*$ )[equation 25].



**Figure 11:** Fixmen's experimental data of the absorption attenuation coefficient per wavelength  $\alpha_{\lambda}$  at critical concentration at different frequencies 5, 7, 10, 15, 21 and 25 MHz for the binary mixture Nitroethane-Isooctane versus the reduced frequency  $\omega^*$  according to the general modification for the analytic function K(y,  $\omega^*$ ).

Figures 10 and 11 show an excellent agreement for large reduced frequency  $\omega^*$  between experimental values and theoretical predictions for the general modified analytic function K(y,  $\omega^*$ ). The correction of the analytic function K(y,  $\omega^*$ ) according to Hornowski theory  $k_{mH}(y, \omega^*)$  is given in equation (26):

$$k_{mH}(y,\omega^*) = \frac{\omega^* + \omega^* \times \sqrt[2]{4 - 4\left[\left(\frac{y^2 + y}{1 + y^2}\right) \times \left[-0.1762 \times \omega^{*^{-0.225}} + 0.5428\right]\right]^2}}{2\left[\left[\frac{y^2 + y}{1 + y^2}\right] \times \left[-0.1762 \times \omega^{*^{-0.225}} + 0.5428\right]\right]}$$
(26)

Figure 12 represents plot of Hornowski experimental absorption attenuation values of  $F(\omega^*)$  versus the reduced frequency  $\omega^*$  for

Nitroethane and Isooctane binary mixture at 5, 7, 10, 15, 21 and 25 MHz frequencies, the new general modification for the analytic function is given in equation (26) along with the theoretical scaling integral  $F(\omega^*)$ .



Figure 12: The experimental data of absorption values of  $F(\omega^*) = \frac{\alpha_\lambda}{\pi u^2(\omega)A(T)}$  versus the reduced frequency  $\omega^*$  for Nitroethane and Isooctane binary mixture at 5, 7, 10, 15, 21 and 25 MHz frequencies according to the new modified Hornowski model of  $k_{mH}(y, \omega^*)$ .

For Mistura theory, the new correction for the modified analytic function  $k_{mM}(y,\omega^*)$  is given by equation (27):

$$k_{mM}(y,\omega^*) = \frac{\omega^* + \omega^* \times \sqrt[9]{559 - 4 \left[ \left( \frac{y^2 + y}{1 + y^2} \right) \times \left[ -0.1762 \times \omega^{* - 0.225} + 0.5428 \right] \right]^2}{2 \left[ \left[ \frac{y^2 + y}{1 + y^2} \right] \times \left[ -0.1762 \times \omega^{* - 0.225} + 0.5428 \right] \right]}$$
(27)

Figure 13 predicts plot of Mistura experimental absorption attenuation values of  $F(\omega^*)$  versus the reduced frequency  $\omega^*$  for Nitroethane and

Isooctane binary mixture at 5, 7, 10, 15, 21 and 25 MHz frequencies, the new general modification for the analytic function  $k_{mM}(y,\omega^*)$  is given in equation (27) along with the theoretical scaling integral  $F(\omega^*)$ .



Figure 13: The experimental data of absorption values of  $F(\omega^*) = \frac{\alpha_{\lambda}}{\pi u^2(\omega)A(T)}$  versus the reduced frequency  $\omega^*$  for Nitroethane and Isooctane binary mixture at 5, 7, 10, 15, 21 and 25 MHz frequencies according to the new modified Mistura model of  $k_{mM}(y,\omega^*)$ .

Finally, for Chapan theory the new correction for the modified analytic function  $k_{mc}(y, \omega^*)$  is given by equation (28):

$$k_{mC}(y,\omega^*) = \frac{\omega^* + \omega^* \times \sqrt[2]{197 - 4\left[\left(\frac{y^2 + y}{1 + y^2}\right) \times \left[-0.1762 \times \omega^{*^{-0.225}} + 0.5428\right]\right]^2}}{2\left[\left[\frac{y^2 + y}{1 + y^2}\right] \times \left[-0.1762 \times \omega^{*^{-0.225}} + 0.5428\right]\right]}$$
(28)

Figure 14 predicts plot of Chapan experimental absorption attenuation values of  $F(\omega^*)$  versus the reduced frequency  $\omega^*$  for Nitroethane and

Isooctane binary mixture at 5, 7, 10, 15, 21 and 25 MHz frequencies, the new general modification for the analytic function  $k_{mc}(y, \omega^*)$  is given in equation (28) along with the theoretical scaling integral  $F(\omega^*)$ .



Figure 14: The experimental data of absorption values of  $F(\omega^*) = \frac{\alpha_{\lambda}}{\pi u^2(\omega)A(T)}$  versus the reduced frequency  $\omega^*$  for Nitroethane and Isooctane binary mixture at 5, 7, 10, 15, 21 and 25 MHz frequencies according to the new modified Chapan model of  $k_{mC}(y, \omega^*)$ .

Figures 12, 13 and 14 show an excellent agreement for large reduced frequency  $\omega^*$  between experimental values and theoretical predictions for the modified analytic function.

At the end of this section we conclude from the results we have in all previous five models of mode- coupling theories that we can unite trend for modification of these theories. We modify the analytic function K(y)

to K(y,  $\omega^*$ ), the experimental data for the five theories have the same shape but differ in the vertical amplitude because the experimental data for F( $\omega^*$ ) depends on the amplitude A(t) as shown in equation (1), and the amplitude A(T) for Fixmen theory equals with Kawasaki theory and also, the amplitude for Mistura, Chapan and Hornowski theories depends on Fixmen and Kawasaki amplitude as shown in equations (20), (21), and equation (22) in addition to other constant parameters for the same binary liquid mixture, so the result we have for the modification analytic function for Mistura, Hornowski and Chapan have the same general formula but it must differ in vertical amplitude.

# **Chapter Five** Conclusion

The ultrasonic attenuation absorption coefficient at critical temperature and critical composition for the critical binary mixture nitroethaneisooctane decreases as the temperature increases for all frequencies. The ultrasonic attenuation absorption coefficient for the critical composition and above critical temperature decreases with increasing frequency at different temperatures. The results of  $\alpha_c f^{-2}$  versus  $f^{-1.06}$  yield a straight line as shown by Ferrell and Bhattacharjee theory. The experimental data of the critical and background parts of the ultrasonic attenuation absorption coefficient as function of the reduced frequency is in a good agreement with the theoretical scaling function as predicted by Ferrell and Bhattacharjee theory. The positive sign for the g factor indicates that the phase separation near the critical point is induced by a sudden increase of pressure.

Mode-coupling theories were used to describe the critical behavior of binary liquid mixtures and above critical point. The analytic function of Fixmen, Kawasaki, Mistura, Hornowski and Chapan theories are not suitable to yield proper scaling function in order to get an agreement with experimental data. The analytic function of Mode-coupling theories K(y) relates to the correlation length  $y = q\xi$ . The disagreement between theoretical and experimental data for Fixmen, Kawasaki, Mistura, Hornowski and Chapan theories for sound propagation in binary liquid mixture is shown in figures 6 to 10. The modified Kawasaki's, Fixmen's,

Mistura's, Hornowski's and Chapan's analytic function depend on the correlation length  $\xi$  and on the shear viscosity  $\mu$ . By Introducing these physical parameters, Fixmen, Kawasaki, Mistura, Hornowski and Chapan theories is improved to describe the critical behavior of binary liquid mixtures above critical temperature and at critical concentration. In order to explain the trend of the experimental data, the modification of the analytic function presents an excellent agreement between theoretical and experimental data for sound propagation in binary liquid mixture.

## References

**1.** Verma N.K., Khanna S. K., and Kapila B., Comprehensive Chemistry XII, Laxmi Publications, p. 212(2005).

Rice O. K., Critical Phenomena in Binary Liquid Systems, Chem. Rev.
 44, 69–92 (1949).

**3.** Manisha Gupta, Shahla Parveen, Maimoona Yasmin and Jagdish Prasad Shukla, Thermoacoustical and excess properties of binary mixtures of ethyl butyrate with methanol and vinyl acetate, international journal of thermodynamics, **13**,  $2 \leq 5$ , 1301-9724, (2010).

**4.** Amani M. J., Gray M. R. & Shaw J. M., Phase behavior of Athabasca bitumen+ water mixtures at high temperature and pressure. The Journal of Supercritical Fluids **77**, 142–152 (2013).

**5.** Bulavin L. A., Bilous O. I., Balega A. V., Svechnikova O. S., Anomalies of the Sound Absorption Coefficient for Binary Solutions with a Critical Stratification Temperature, Ukrainian Journal of Physics, **63**, 4, (2018).

**6.** Bahadur Alisha S., Ramesh B. V., Krishna Rao K. S. V., Subha M. C. S., Chowdoji Rao K., Ultrasonic Studies on Binary Liquid Mixtures of Cyclohexane with Carbitols at 308.15 K°, Indian Journal of Advances in Chemical Science, **5**, 3, 155- 159 (2017).

**7.** Abdelraziq I. R., Bsharat H. Y., Critical Behavior of Refractive Index of Binary Mixture Cyclohexane-Phenol. PCAIJ, **10**, 2, 046-057 (2015).

## 39

**8.** Arvind P. Jogdand, Dielectric Behavior of Acetonitrile + N-Butyl Alcohol Binary Mixtures at Microwave Frequency at 10 C°, Journal of Applied Physics, **11**, 2, 2278-4861 (2019).

**9.** Botchand W., and Fixman M., "Sound Absorption in Gases in the Critical Region", J. Chem. Phys. **42**, 199 (1965).

**10.** Talmaciu A. I., Ravber M., Volf I., Knez Ž. & Popa V. I., Isolation of bioactive compounds from spruce bark waste using sub- and supercritical fluids. The Journal of Supercritical Fluids **117**, 243–251 (2016).

**11.** Tarakowski R., Malanowski A., Kościesza R. & Siegoczyński R. M., {VIS} spectroscopy and pressure induced phase transitions – Chasing the olive oils quality. Journal of Food Engineering **122**, 28–32 (2014).

**12.** Corberi F., Gonnella G. & Piscitelli A., Singular behavior of fluctuations in a relaxation process. Journal of Non-Crystalline Solids **407**, 51–56 (2015).

**13.** Abderaziq I., Two Binary Liquid Critical Mixtures Belong to Class of Universality, J Material Science Engineering, **5**, 1, (2015).

**14.** Ali A., Nain A. K., Chand D. & Ahmad R., Volumetric, ultrasonic and viscometric studies of molecular interactions in binary mixtures of aromatic+ aliphatic alcohols at different temperatures. Physics and Chemistry of Liquids **43**, 205–224 (2005).

**15.** Bulavin L. A., Belous O. I. & Svechnikova O. S., Attenuation near the critical point of n-pentanol-nitromethane solution stratification. Ukr. J. Phys **61**, 375–380 (2016).

**16.** Ferrell R. & Bhattacharjee J., Dynamic scaling theory of the critical attenuation and dispersion of sound in a classical fluid: The binary liquid. Physical Review A **31**, 1788 (1985).

**17.** Fisher M. E. & Burford R. J., Theory of Critical-Point Scattering and Correlations. I. The Ising Model. Physical Review **156**, 583–622 (1967).

**18.** Fixman M., Absorption and dispersion of sound in critical mixtures. The Journal of Chemical Physics **36**, 1961–1964 (1962).

**19.** Hornowski T. and Madej D., Dynamic universality of critical attenuation in benzonitrte isooctane and nitroehane isooctane binary mixture, Journal of Physics: Condensed matter, **14**, 50, (2002).

**20.** Ali A., Nain A. K., Sharma V. K. and Ahmad S., ultrasonic studies in binary liquid mixtures, Indian journal of physics, **75(B)**, 6, 519-525 (2001).

**21.** Murata K. & Tanaka H. Liquid--liquid transition without macroscopic phase separation in a water--glycerol mixture. Nature materials **11**, 436–443 (2012).

**22.** Bhattacharjee J. & Iwanowski I., Bulk viscosity universality and scaling function near the binary liquid consolute point. The Journal of chemical Physics, **131**, 17, (2009).

**23.** Maksimochkin G. I., Pasechnik S. V & Maksimochkin A. G., Ultrasonic studies of structural transformations and phase transitions in liquid crystal emulsions. Acoustical Physics **57**, 264–270 (2011).

**24.** Yixing Zhong, Yayun Zhuo, Zhenfeng Wang, Yong Sha, Marangoni convection induced by simultaneous mass and heat transferduring evaporation of n-heptane/ether binary liquid mixture, International Journal of Heat and Mass Transfer **108**, 812–821 (2017).

**25.** Xiaogang Yang , Yuezheng Gong, Jun Li , Jia Zhao, Qi Wang, On hydrodynamic phase field models for binary fluid mixtures. Theoretical Computational Fluid Dynamics, **32**, 537–560 (2018).

**26.** Bhattacharjee J., Mirzaev S. & Kaatze U., Does the Viscosity Exponent Derive from Ultrasonic Attenuation Spectra? International Journal of Thermophysics, **33**, (2012).

**27.** Anisimov M. A., Universality versus nonuniversality in asymmetric fluid criticality. Condense Matter Physics**16**, 2, 23603 (2013).

**28.** Vctor H. Alvarez Silvana Mattedi, Manuel Martin-Pastor, Martin Aznar, Miguel Iglesias, Thermophysical properties of binary mixtures of {ionic liquid 2-hydroxy ethylammonium acetate + (water, methanol, or ethanol)}, J. Chem. Thermodynamics **43**, 997–1010 (2011).

**29.** Gyan Prakash Dubey, Prabjot Kaur, Molecular interactions in binary mixtures of 1-butoxy-2-propanol with alcohols at different temperatures: A

thermophysical and spectroscopic approach, J. Chem. Thermodynamics **79**, 100–108 (2014)

**30.** Pietrzak A., Piekarski H., Molar heat capacities for {isomer of butanediol + methanol} as function of mixture composition and temperature, J. Chem. Thermodynamics **79**, 171–177 (2014).

**31.** Somenath Panda, Sudipta Ray, Venkatramana Losetty 1, Ramesh L. Gardas, Synthesis and thermophysical properties of pyrrolidonium based ionic liquids and their binary mixtures with water and DMSO at T=(293.15 to 333.15 K°, Journal of Molecular Liquids **224**,882–892 (2016).

**32.** Jose F. Martínez-Lopez, Severin Schneider, Daniel Salavera, Ana M. Mainar Jose S., Urieta Juan I. Pardo, Molar heat capacities of the mixture {1,8-cineole + ethanol} at several temperatures and atmospheric pressure, J. Chem. Thermodynamics **92**, 146–15 (2016).

**33.** Kai-Ling Liang, Rhoda B. Leron, Meng-Hui Li, Heat capacities of aqueous binary and ternary mixtures (with piperazine) of N-(2-aminoethyl)-piperazine and N,N,N0-trimethylethylenediamine at temperatures (303.2–353.2) K, J. Chem. Thermodynamics **103**, 51–58, (2016).

**34.** Heena Gupta, Jyoti Kataria, Dimple Sharma, Vinod Kumar Sharma, Topological investigations of molecular interactions in binary ionic liquid mixtures with a common ion: Excess molar volumes, excess isentropic compressibilities, excess molar enthalpies and excess molar heat capacities, J. Chem. Thermodynamics **103**, 189–205 (2016).

**35.** Yimin Guo, Xianshuo Zhang, Chen Xu, Weiguo Shen, Liquid-liquid phase equilibrium and heat capacity of binary solution {2-propanol + 1- octyl-3 methylimidazo m hexafluorophosphate}, J. Chem. Thermodynamics **105**, 434–442 (2017).

**36.** Huan Shen, Songgu Wu, Yumin Liu, Kangli Li, Shijie Xu, Junbo Gong, Determination and correlation of Avermectin B1a solubility in different binary solvent mixtures at temperatures from (283.15 to 313.15) K, J. Chem. Thermodynamics **105**, 253–266 (2017).

**37.** Latifa Negadi, Badra Feddal-Benabed, Indra Bahadur, Joseph Saab, Manel Zaoui-Djelloul-Daouadji, Deresh Ramjugernath, Amina Negadi, Effect of temperature on density, sound velocity  $u(\omega)$ , and their derived properties for the binary systems glycerol with water or alcohols, The Journal of Chemical Thermodynamics, **109**, 124-136 (2017).

**38.** Pousaneh F., Edholm O. & Maciołek, A., Molecular dynamics simulation of a binary mixture near the lower critical point. The Journal of Chemical, **145**, 1, 014501 (2016).

**39.** Bulavin L. A., Belous O. I, Chalyi A.V., Anomalous propagation and scattering of sound in 2-propanol water solution near its singular point, Journal of Molecular Liquids **235**, 24–30(2017).

**40.** Abdelraziq I. R., Critical Amplitude of Acoustical Attenuation in Mode-Coupling Theory for the Binary Mixture Aniline and Cyclohexane, An-Najah Univ. J. Res. **15**, 11 (2001).

**41.** Abdelraziq I. R., Ultrasonic Absorption in Critical Binary.Mixture.of.Perfluoromethylcyclo. hexane+Carbon trachlori e", J. Acoust. Soc. Am. **107**, 2, 788-92 (2000).

**42.** Abdelraziq, I. R., "Critical Behavior of the Ultrasonic Attenuation for the Binary Mixtures of Benzene+Coconut Oil and Hexane - dichloroethyl ether", Acta Acustica united with Acustica, **91**, 4, 716-722 (2005).

**43.** Abdelraziq I. R., Yun S. S., and Stumpf F. B., Critical Behavior of the Ultrasonic Attenuation and Velocity and Shear Viscosity for the Binary Mixture of Carbon Tetrachloride + Coconut Oil, J. Acoust. Soc. Am. **91**, 2, 844 (1992).

**44.** Garland C. and Sanchez G., Ultrasonic Study of Critical Behavior in The Binary Liquid 3Methylpentane nitroethane, J. Chem. Phys. **79**, 3090 (1983).

**45.** Abdelraziq I. R., Yun S. S., and Stumpf F. B., Critical Behavior of the Ultrasonic Attenuation and Velocity and Shear Viscosity for the Binary Mixture of Nitrobenzene+n Hexane, J. Acoust. Soc. Am. **88**, 1831 (1990).

**46.** Abdelraziq I. R., Musameh S., Abu-Jafar M., Shear Viscosity Anomaly Near the Critical Binary System, BethLahem U. J., **16**, 70-78 (1996).

**47.** Abdelraziq I. R., Concentration and Temperature Dependence of Shear Viscosity of the Critical Mixture of Nitroethane and 3- Methylpentanell, An-Najah Univ. J. Res. (N. Sc). **16**, 2, (2002).

**48.** Abdelraziq, I. R., The Behavior of the Ultrasonic of the Cyclohexane and Aniline<sup>I</sup>, Islamic R. J., **4**, 2, 91-105 (1996).

**49.** D'Arrigo G. & Paparelli A., Ultrasonic spectroscopy in nonionic micellar solutions far from and near to Tc. Physical Review E, **50**, 6, 4817-4826 (1994).

**50.** Kroll D. M. and Ruhland, Sound propagation in critical binary mixtures, J. M. Physical Review A **23**, 371(1981).

51. Fixman M., Absorption and Dispersion of Sound in Critical Mixtures,J. Chem. Phys. 36, 1957 (1962).

**52.** Kawasaki K., Sound Attenuation and Dispersion near the Liquid Gas Critical Point, Physical Review A, **1**, 1750 (1970).Shiwa Y. and Kawasaki K., Progr.Theor. Phys., **66**, 406 (1981).

**53.** Fuchs M., Gotze W., and Mayr M. R., —Asymptotic Laws for Tagged-Particle Motion in Glassy Systems<sup>I</sup>, Physical Review E **58**, 3384 (1998).

**54.** Mistura L., Sound Propagation near a Critical Point in Multicomponent Systems, J. Chem. Phys. **57**, 2311 (1972).

**55.** Hornowski T. and Labowski M., "Velocity Dispersion and Attenuation of Acoustic Waves in Critical Mixtures", Acta Acustica united with Acustica, **72**, 2, 96-100 (1990).

**56.** Onuki A., Phase transition dynamics. Cambridge University Press, **724** 1109 (2002).

**57.** Folk R., Moser G., Critical sound in fluids and mixtures, Condensed Matter Physics, **2**, 18, 243–254 (1999).

**58.** Bulavin L. A., Belous O. I, Chalyi A.V., Anomalous propagation and scattering of sound in 2-propanol water solution near its singular point, Journal of Molecular Liquids **235**, 24–30 (2017).

**59.** Guixiang Ma, Shang Liu, Shaolei Xie, Yan Jing, Quanyou Zhang, Jinhe Sun, Yongzhong Jia, Binary eutectic mixtures of stearic acid-n-butyramide/n-octanamide as phase change materials for low temperature solar heat storage, Applied Thermal Engineering, **111**, 1052–1059 (2017).

**60.** Bhattacharya A. C. and Deo B. B., Ultrasonic propagation in multicomponent system in the critical region, Pramana, **21**, 4, 273-282 (1983).

**61.** Krivokhizha S. V., Sabirov L., and Turakulov Ya., Temperature dependence of the velocity and absorption of hypersound in the critical region of binary mixtures, Sov. Phys. JETP **51**, 4, (1980).

**62.** Fangfang Shen, Dingqiang Lu, Xiuquan Ling, XinxianWang, Tongqi Liu, Tianhua Huang and Kefei He, Thermodynamic analysis and calculation of solubility of Memantine hydrochloride in ethanol plus (acetonitrile, water, ethyl acetate) binary solvent mixtures, Journal of Molecular Liquids **229**, 58-66 (2017).

**63.** Kandil M. E., Al-Saifi N. M. & Sultan A. S., Simulation and measurements of volumetric and phase behavior of carbon dioxide + higher alkanes at high pressure: {CO2} + n-decane at temperatures (313–410) K and pressures up to 76 {MPa}. International Journal of Greenhouse Gas Control **53**, 198–206 (2016).

**64.** Srinivasu J. V., Narendra K., Kavitha Ch., Srinivasa Krishna T. and Subba Rao B., "Molecular interactions in binary liquid mixtures – an ultrasonic study", J. Pure Apple Ultrason **39**, 35-39 (2017).

**65.** Bhattacharjee J. K., Udo Kaatze, and Sirojiddin Z. Mirzaev, "Sound Attenuation Near the Demixing Point of Binary Liquids: Interplay of

Critical Dynamics and Noncritical Kinetics", Reports on Progress in Physics, **73**, 6, (2010).

**66.** Hornowski T. and Madej D., Ultrasonic Studies of Critical Concentration Fluctuations in Benzonitrile-Isooctane Mixture, J.Chem. Phys., **269**, 303-311(2001).

**67.** Pawar N. R., Chimankar O. P., Bhandakkar V. D. and Padole N. N. Ultrasonic velocity and absorption study of binary mixtures of cyclohexane with acrylonitrile by interferometric method at different frequencies, IOP Conf. Series: Materials Science and Engineering **42**,012030, (2012).

**68.** Sandhya Sri PB, Zareena Begum and Rambabu C., Theoretical Evaluation of Ultrasonic Velocities in Binary Liquid Mixtures of Anisic Aldehyde with some Esters at Different Temperatures Using Different Theories and Models, J Thermodyn Catal **4**, 1, (2013),

**69.** Thorsten Hiester, Dietrich S., and Klaus Mecke, Microscopic theory for interface fluctuations in binary liquid mixtures, The Journal of Chemical Physics, **125**, 18, 184701(2006).

**70.** Mirzaev S. Z., Iwanowski I., Kaatze U., Dynamic scaling and background relaxation in the ultrasonic spectra of the ethanol–dodecane critical mixture, Chemical Physics Letters **435**, 263–267 (2007).

**71.** Amalendu Pal, Mohit Saini, Bhupinder Kumar, Volumetric, ultrasonic and spectroscopic (FT-IR) studies for the binary mixtures of imidazolium based ILs with 1,2-propanediol, Fluid Phase Equilibria **411**, 66-73 (2016).

**72.** Dongren Cai, Jinbei Yang, Hairong Da, Ling Li, Hongxing Wang, Ting Qiu, Densities and viscosities of binary mixtures N, N-dimethyl-N-(3-

sulfopropyl)cyclohexylammonium tosylate with water and methanol at T =  $(303.15 \text{ to } 328.15) \text{ K}^{\circ}$ , Journal of Molecular Liquids **229**, 389–395 (2017).

**73.** Jian Gong and Jun Liu, Mechanical transitional behavior of binary mixtures via DEM: Effect of differences in contact-type friction coefficients, Computers and Geotechnics **85** 1-14 (2017).

**74.** Sharma V. K., Baghour S., Solanki S., Sharma D., Excess heat capacities of (binary + ternary) mixtures containing [emim][BF4] and organic liquids, J. Chem. Thermodynamics **79**, 19-32 (2014).

**75.** Fenner D. B., Nonsingular absorption of ultrasound near the critical mixing point of a binary liquid. Physical Review A **23**, 1931–1940 (1981).

**76.** Bhattacharjee J. K. & Kaatze U., Fluctuations Near the Critical Micelle Concentration. I. Premicellar Aggregation, Relaxation Rate, and Isentropic Compressibility. The Journal of Physical Chemistry B **117**, 3790–3797 (2013).

**77.** Hill R. M., Plastic Behaviour of Sheet Metal. Phys. Stat. Sol. **231** (1981).

78. Martin Trusler, Physical Acoustics and Metrology of Fluids, 1<sup>st</sup> edition,
B:CRC Press, 259,(1991).

**79.** Tanaka H., Wada Y. & Nakajima H., Acoustic anomaly in a critical binary mixture of aniline and cyclohexane at low and ultrasonic frequencies. Chemical Physics, **68**, 1-2, 223-231 (1982).

جامعة النجاح الوطنية

كلية الدراسات العليا

# تعديل الاقتران التحليلي لنظرية كافازاكي في مخاليط السوائل الثنائية

اعداد

رويدة محمود عيسى صادق

اشراف أ. د. عصام راشد عبد الرازق

د. محمد ابو جعفر

قدمت هذه الرسالة استكمالا لمتطلبات الحصول على درجة الدكتوراة في الفيزياء بكلية الدراسات العليا في جامعة النجاح الوطنية في نابلس – فلسطين 2019

# تعديل الاقتران التحليلي لنظرية كافازاكي في مخاليط السوائل الثنائية اعداد رويدة محمود عيسى صادق اشراف أ. د. عصام راشد عبد الرازق أ. د. محمد ابو جعفر الملخص

لقد تم استخدام النتائج العملية المقاسة للاضمحلال الصوتي لدراسة نظرية فيكسمان وكافازاكي ومستورا وشبان وهرنوسكي التي تختص بالسوائل ثنائية المخاليط عند النقطة الحرجة. واظهرت النتائج ان النظريات الخمس المذكورة انفا لم تتجح في وصف السلوك الحرج بشكل يتوافق مع النتائج التجريبية خاصة عند الترددات العالية للخليط الثنائي نيتروايثان- ايسواوكتان، تم تعديل الاقتران التحليلي لنظريات فيكسمان وكافازاكي ومستورا وشبان وهرنوسكي واسهم هذا التعديل في تغيير شكل الاقتران الاتزاني ليتوافق مع شكل الاقتران الاتزاني التجريبي.